

 **LIUGONG**

870HE



BATTERY TYPE	LFP
RATED STORAGE ENERGY	423 kWh
OPERATING WEIGHT	24,264 kg
RATED LOAD CAPACITY	7,500 kg
STANDARD BUCKET SIZE	4.7 m ³
STANDARD BREAKOUT FORCE	221 kN
STANDARD DUMP CLEARANCE	3,101 mm



B A T T E R Y E L E C T R I C V E H I C L E

TOUGH WORLD. TOUGH EQUIPMENT.

POWER BATTERY

Battery Type	LFP
Rated Storage Energy	423 kWh
Nominal Voltage	618V
System Voltage	DC24V
BMS Protection Level	IP67
Cooling Type	Intelligent temperature control liquid cooling
Recommended Charger	≤360 kW
Charging Time (300 kW Charging pile)	≤90 min

DRIVE MOTOR

Peak Power	160 kW
Protection Level	IP67
Ambient Temperature	-40~85°C
Cooling Type	Intelligent temperature control liquid cooling
Altitude	≤5000 m

HYDRAULIC MOTOR

Peak Power	160 kW
Protection Level	IP67
Ambient Temperature	-40~85°C
Cooling Type	Intelligent temperature control liquid cooling
Altitude	≤5000 m

TRANSMISSION

Manufacturer	LiuGong
Number of Speeds, fwd / rev	2 / 2
Maximum Travel Speed, fwd	40 km/h
Maximum Travel Speed, rev	14 km/h
Transmission Type	Planetary electric control shift

AXLES

Type	LiuGong wet axle
Axle Oscillation	± 9.5°
Tire Size	26.5R25 ★★ L-3

WORKING HYDRAULICS

System	Fixed&Variable dual pump confluent
Operation	Single electric-control joystick
Work Pump	Gear
Work Pressure	Boom cylinder: 28 MPa Curl cylinder: 25 MPa

STEERING HYDRAULICS

System	Flow amplifier
Steering Pump	Piston variable pump
Steering Relief Pressure	21 MPa

BRAKES

Service Brake Type	Full hydraulic brake
Service Brake Actuation	Hydraulic wet brake
Parking Brake Type	Drum
Parking Brake Actuation	Hydraulic brake cylinder

LOADER ARM PERFORMANCE

Operating Weight	24,264 kg
Bucket Capacity	4.7 m³
Tipping Load - Straight	18,982 kg
Tipping Load - Full Turn	16,764 kg
Raise Time	5.2 s
Dump Time	1.3 s
Float Down Time	3 s
Fastest Total Cycle Time	9.5 s
Bucket Breakout Force	221 kN
A Maximum Hinge Pin Height	4,470 mm
B Dump Clearance at Full Height Discharge	3,101 mm
C Dump Reach at Full Height Discharge	1,257 mm
D Maximum Digging Depth, Bucket Level	119 mm
S ₁ Bucket Rollback at Ground Level	45°
S ₂ Bucket Rollback at Carry	50°
S ₃ Bucket Rollback at Maximum Height	58°
S ₄ Maximum Dump Angle at Full Height	45°

DIMENSIONS

E Ground Clearance	460 mm
G Wheelbase	3,715 mm
H Cab Height	3,550 mm
J Wheel Tread	2,380 mm
K Width over Tires	3,050 mm
L Length with Bucket Down	8,957 mm
M Turn Angle, Either Side	38°
P Rear Angle of Departure	28°
R ₁ Turning Radius, Bucket Carry	7,577 mm
R ₂ Turning Radius, Outside of Tire	6,946 mm
W Width over Bucket	3,160 mm

SERVICE CAPACITIES

Anti-freeze	45 L
Hydraulic Reservoir	284 L
Axle, Front / Rear	63 L / 63 L
Transmission	23 L

