



## Multi purpose lithium grease.

### APPLICATIONS

Multi purpose grease

General Lubrication

Recommendation

- **LEX 2** is a multipurpose grease for general lubrication under normal operating conditions and loads, formulated for lubrication of all kinds of universal applications in transport, agriculture and off road equipment, operating in wet, dusty and/or dry conditions.
- Lubrication of all kinds of bearings and joints when the temperature and loading conditions are normal.
- Pre-eminently suitable for passenger car, light truck and leisure vehicle applications.
- Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

### ADVANTAGES

Miscible

Pumpability

No harmful substances

- **LEX 2** is miscible with most other conventional soap greases.
- Excellent mechanical stability avoiding ejection or loss of consistency during operation.
- Excellent pumpability due to the low temperature characteristics and smooth texture.
- Very good water resistance, even in a humid environment a sufficient lubricating film will be maintained.
- **LEX 2** does not contain lead, or other heavy metals considered harmful to human health and the environment.

### CHARACTERISTICS

	METHODS	UNITS	LEX 2
Soap/ Thickener		-	Lithium
NLGI Grade	ASTM D 217/DIN 51 818	-	2
Colour	Visual	-	Glazy Yellow
Appearance	Visual	-	Smooth
Operating Temperature range		°C	-25 to 120
Penetration @ 25 °C	ASTM D 217/DIN51 818	0.1 mm	265-295
Anti-rust performance SKF- EMCOR	DIN 51 802/IP220/NFT 60-135/ISO 11007	rating	0-0
Dropping point	IP 396/DIN ISO 2176	°C	≥185
Kinematic viscosity of the base oil at 40°C	ASTM D 445/DIN 51 562-1/ISO 3104/IP71	mm <sup>2</sup> /s (cSt)	150

The typical characteristics mentioned represent mean values

### SPECIFICATIONS

ISO 6743-9: L-XBCEA 2

DIN 51 502: K2K -25

## LEX 2

N° TDS/DXB/09/10/333

TOTAL MARKETING MIDDLE EAST  
Dubai, UAE  
1/1

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available at [www.quickfds.com](http://www.quickfds.com)